


Series: LKRA-VPA, BKRA-VPA, wheel Ø 125 - 150 mm

Light duty swivel and fixed castors with bolt hole fitting, heavy brackets

 80 - 110 kg



3



Brackets: LKRA/BKRA Series - Pressed steel, swivel bracket with double ball bearing in the swivel head, strong central kingpin, bolted wheel axle, zinc-plated.
Detailed description: Page 60 and 76.

Wheels: VPA Series - Tyres: Solid rubber, colour grey, non-marking, 80° shore A.
Rims: Plain bearing version made of high-quality nylon. Ball bearing version made of polypropylene. Shock and impact-resistant, corrosion-resistant, colour black.
Detailed description: Page 92 and 30.

Swivel castors		Fixed castors		Swivel castors with "stop-fix" brake		Wheel Ø [mm]	Tyre width [mm]	Load capacity [kg]	Bearing version	Total height [mm]	Plate Ø [mm]	Bolt hole Ø [mm]	Offset swvl castor [mm]
Ref. No.		Ref. No.		Ref. No.									
LKRA-VPA 125G		BKRA-VPA 125G		LKRA-VPA 125G-FI		125	25	80	Plain bearing	158	57	13	40
LKRA-VPA 125G-11				LKRA-VPA 125G-11-FI		125	25	80	Plain bearing	158	57	11	40
LKRA-VPA 125K		BKRA-VPA 125K		LKRA-VPA 125K-FI		125	25	80	Ball bearing	158	57	13	40
LKRA-VPA 125K-11				LKRA-VPA 125K-11-FI		125	25	80	Ball bearing	158	57	11	40
LKRA-VPA 126G		BKRA-VPA 126G		LKRA-VPA 126G-FI		125	32	100	Plain bearing	158	57	13	40
LKRA-VPA 126G-11				LKRA-VPA 126G-11-FI		125	32	100	Plain bearing	158	57	11	40
LKRA-VPA 126K		BKRA-VPA 126K		LKRA-VPA 126K-FI		125	32	100	Ball bearing	158	57	13	40
LKRA-VPA 126K-11				LKRA-VPA 126K-11-FI		125	32	100	Ball bearing	158	57	11	40
LKRA-VPA 150G		BKRA-VPA 150G		LKRA-VPA 150G-FI		150	32	110	Plain bearing	182	57	13	40
LKRA-VPA 150G-11				LKRA-VPA 150G-11-FI		150	32	110	Plain bearing	182	57	11	40
LKRA-VPA 150K		BKRA-VPA 150K		LKRA-VPA 150K-FI		150	32	110	Ball bearing	182	57	13	40
LKRA-VPA 150K-11				LKRA-VPA 150K-11-FI		150	32	110	Ball bearing	182	57	11	40

Variants / Accessories



	Antistatic version, black tyre	With pressed steel thread guard, zinc-plated	With electrostatic powder coating	With threaded pin M12 x 30	With metal expander fitting
Technical description page	30	79		74	75
Ref. No. extension	-EL	-FA		-GS12	See below
Available for wheel Ø [mm]	All ball bearing versions	All sizes	Upon request	All swivel castors	All with bolt hole Ø 11 mm

Metal expander fitting

Internal tube dim. round tube [mm]	Internal tube dim. square tube [mm]	Ref. No. extension
17 - 19	17 - 19	-E11
20 - 25	18 - 21	-E12
25 - 30	21 - 25	-E13
30 - 35	25 - 29	-E14
35 - 40	29 - 32	-E15
39 - 45	32 - 38,5	-E17